

## SECTION 10 26 00 - WALL AND DOOR PROTECTION

### PART 1 - GENERAL

#### 1.1 SUMMARY

- A. This Section includes the following:
  - 1. Wall guards.
  - 2. Corner guards.
  - 3. Impact-resistant wall coverings.

#### 1.2 SUBMITTALS

- A. Product Data: For each type of product indicated.
- B. Shop Drawings: Include sections, details, and attachments to other work.
- C. Samples: For each type of unit and for each color and texture required.
- D. LEED Submittals:
  - 1. Credit EQ 4.1: Manufacturers' product data for adhesives, including printed statement of VOC content.
- E. Maintenance data.

#### 1.3 QUALITY ASSURANCE

- A. Fire-Test-Response Characteristics: Provide impact-resistant, plastic wall-protection units with surface-burning characteristics as determined by testing identical products per ASTM E 84, NFPA 255, or UL 723 by UL or another testing and inspecting agency acceptable to authorities having jurisdiction.

#### 1.4 DELIVERY, STORAGE, AND HANDLING

- A. Store plastic wall-protection components for a minimum of 72 hours, or until plastic material attains a minimum room temperature of 70 deg F.

## 1.5 WARRANTY

- A. Special Warranty: Manufacturer's standard form in which manufacturer agrees to repair or replace components of impact-resistant wall-protection units that fail in materials or workmanship within specified warranty period.

- 1. Warranty Period: Five years from date of Substantial Completion.

## PART 2 - PRODUCTS

### 2.1 MANUFACTURERS

- A. In other Part 2 articles where titles below introduce lists, the following requirements apply to product selection:
  - 1. Manufacturers: Subject to compliance with requirements, provide products by one of the manufacturers specified.

### 2.2 MATERIALS

- A. Extruded Rigid Plastic: High-impact-resistant PVC or acrylic-modified vinyl plastic with integral color throughout.
- B. Plastic Sheet Wall Covering Material: Semirigid, high-impact-resistant PVC or acrylic-modified vinyl plastic sheet with integral color throughout.
- C. Aluminum Extrusions: ASTM B 221.
- D. Stainless-Steel Sheet: ASTM A 240/A 240M.
- E. Fasteners: Aluminum, nonmagnetic stainless steel, or other noncorrosive metal; security-type where exposed to view.
- F. Adhesive: Type recommended by manufacturer for use with material being adhered to substrate indicated.
  - 1. Use adhesives and sealants that comply with the following limits for VOC content when calculated according to 40 CFR 59, Subpart D (EPA Method 24):
    - a. Gypsum Board and Panel Adhesives: 50 g/L.
    - b. Multipurpose Construction Adhesives: 70 g/L.
    - c. Contact Adhesive: 250 g/L.

### 2.3 WALL GUARDS

- A. Crash Rail: Heavy-duty assembly consisting of continuous snap-on plastic cover installed over continuous retainer; with continuous rubber or vinyl bumper cushion(s) centered in the retainer; designed to withstand impacts.

1. Manufacturers:
    - a. American Floor Products Co., Inc.
    - b. ARDEN Architectural Specialties, Inc.
    - c. Balco, Inc.
    - d. Construction Specialties, Inc.
    - e. IPC Door and Wall Protection Systems; Division of InPro Corporation.
    - f. Korogard Wall Protection Systems; Division of RJF International Corporation.
    - g. Pawling Corporation.
    - h. Or approved equal
  2. Cover: Extruded rigid plastic, minimum 0.100-inch wall thickness; in dimensions and profiles indicated on Drawings.
  3. Retainer: Minimum 0.080-inch- thick, 1-piece, extruded aluminum.
    - a. Mounting: Surface mounted directly to wall.
  4. End Caps and Corners: Prefabricated, injection-molded plastic; color matching cover; field adjustable for close alignment with snap-on cover.
  5. Accessories: Concealed splices and mounting hardware.
- B. Rub Rail: Assembly consisting of continuous snap-on cover installed over continuous retainer.
1. Manufacturers:
    - a. American Floor Products Co., Inc.
    - b. ARDEN Architectural Specialties, Inc.
    - c. Balco, Inc.
    - d. Boston Retail Products.
    - e. Construction Specialties, Inc.
    - f. IPC Door and Wall Protection Systems; Division of InPro Corporation.
    - g. Pawling Corporation
    - h. Or approved equal.
  2. Cover: Extruded flexible vinyl, minimum 0.078-inch wall thickness; in dimensions and profiles indicated on Drawings.
  3. Retainer: Minimum 0.0625-inch- thick, 1-piece, extruded aluminum.
    - a. Mounting: Surface mounted directly to wall.
  4. End Caps and Corners: Prefabricated, injection-molded plastic; color matching cover; field adjustable for close alignment with snap-on cover.
  5. Accessories: Concealed splices and mounting hardware.
- 2.4 CORNER GUARDS
- A. Surface-Mounted, Resilient, Plastic Corner Guards: Assembly consisting of snap-on plastic cover installed over continuous retainer; including mounting hardware; fabricated with 90- or 135-degree turn to match wall condition.

1. Manufacturers:
    - a. American Floor Products Co., Inc.
    - b. ARDEN Architectural Specialties, Inc.
    - c. Balco, Inc.
    - d. Construction Specialties, Inc.
    - e. IPC Door and Wall Protection Systems; Division of InPro Corporation.
    - f. Korogard Wall Protection Systems; Division of RJF International Corporation.
    - g. Pawling Corporation.
    - h. Or approved equal
  2. Cover: Extruded rigid plastic, minimum 0.100-inch wall thickness;
    - a. Profile: Nominal 2-inch- long leg and 1/4-inch corner radius.
    - b. Height: 8 feet.
    - c. Color and Texture: As selected by University from manufacturer's full range.
  3. Retainer: Minimum 0.060-inch- thick, 1-piece, extruded aluminum.
  4. Top and Bottom Caps: Prefabricated, injection-molded plastic; color matching cover; field adjustable for close alignment with snap-on cover.
- B. Surface-Mounted, Metal Corner Guards: Fabricated from 1-piece, formed or extruded metal with formed edges; with 90- or 135-degree turn to match wall condition.
1. Manufacturers:
    - a. American Floor Products Co., Inc.
    - b. ARDEN Architectural Specialties, Inc.
    - c. Balco, Inc.
    - d. Boston Retail Products.
    - e. Construction Specialties, Inc.
    - f. IPC Door and Wall Protection Systems; Division of InPro Corporation.
    - g. Pawling Corporation.
  2. Material: Stainless steel, Type 304.
    - a. Thickness: Minimum 0.0500 inch.
    - b. Finish: Directional satin, No. 4.
  3. Wing Size: Nominal 2-1/2 by 2-1/2 inches.
  4. Corner Radius: 1/8 inch.
  5. Mounting: Flat-head, countersunk screws through factory-drilled mounting holes.

## 2.5 IMPACT-RESISTANT WALL COVERINGS

- A. Semirigid, Impact-Resistant Sheet Wall Covering: Fabricated from plastic sheet wall covering material.
1. Manufacturers:
    - a. American Floor Products Co., Inc.
    - b. ARDEN Architectural Specialties, Inc.

- c. Balco, Inc.
  - d. Construction Specialties, Inc.
  - e. IPC Door and Wall Protection Systems; Division of InPro Corporation.
  - f. Korogard Wall Protection Systems; Division of RJF International Corporation.
  - g. Pawling Corporation.
- 2. Size: 48 by 96 inches for sheet and 48 by 120 inches for roll.
  - 3. Sheet Thickness: 0.028 inch.
  - 4. Color and Texture: As selected by University from manufacturer's full range.
  - 5. Trim and Joint Moldings: Extruded rigid plastic that matches sheet wall covering color.
  - 6. Mounting: Adhesive.

### PART 3 - EXECUTION

#### 3.1 INSTALLATION

- A. Complete finishing operations, including painting, before installing impact-resistant wall-protection system components.
- B. Install impact-resistant wall-protection units level, plumb, and true to line without distortions. Do not use materials with chips, cracks, voids, stains, or other defects that might be visible in the finished Work.
  - 1. Provide splices, mounting hardware, anchors, and other accessories required for a complete installation.
- C. Immediately after completion of installation, clean plastic covers and accessories using a standard, ammonia-based, household cleaning agent.
- D. Remove excess adhesive using methods and materials recommended in writing by manufacturer.

**END OF SECTION 10 26 00**