

## PART 1 – GENERAL

### 1.1 SUMMARY

A. Section Includes:

1. Corkboard roll goods.
2. Dry Erase boards.

### 1.2 ACTION SUBMITTALS

A. Product Data: For each type of product.

1. Include data on physical characteristics, durability, fade resistance, and fire-test-response characteristics.

B. Samples for Verification: For each type of wall covering and for each color, pattern, texture, and finish specified, full width by 12 inches long in size.

### 1.3 CLOSEOUT SUBMITTALS

A. Maintenance Data: For wall coverings to include in maintenance manuals.

### 1.4 FIELD CONDITIONS

A. Environmental Limitations: Do not deliver or install wall coverings until spaces are enclosed and weathertight, wet work in spaces is complete and dry, work above ceilings is complete, and temporary HVAC system is operating and maintaining ambient temperature and humidity conditions at levels intended for occupants after Project completion during the remainder of the construction period.

B. Lighting: Do not install wall covering until lighting that matches conditions intended for occupants after Project completion is provided on the surfaces to receive wall covering.

C. Ventilation: Provide continuous ventilation during installation and for not less than the time recommended by wall-covering manufacturer for full drying or curing.

## PART 2 – PRODUCTS

### 2.1 PERFORMANCE REQUIREMENTS

A. Low-Emitting Materials: Wall-covering system shall comply with the testing and product requirements of the California Department of Public Health's (formerly, the California Department of Health Services') "Standard Method for the Testing and Evaluation of Volatile Organic Chemical Emissions from Indoor Sources Using Environmental Chambers."

B. Fire-Test-Response Characteristics: As determined by testing identical wall coverings applied with identical adhesives to substrates according to test method indicated below by a qualified testing agency. Identify products with appropriate markings of applicable testing agency.

1. Surface-Burning Characteristics: Comply with ASTM E 84; testing by a qualified testing agency. Identify products with appropriate markings of applicable testing agency.

## 2.2 WALL COVERING

- A. Basis of Design Product: Subject to compliance with requirements, provide TAC-WALL by Walltakers (800-820-9255) or comparable product by the following:
1. Forbo Linoleum Bulletin Boards
  2. Or Approved Equal

## 2.3 DRY ERASE BOARD

- A. Basis of Design Product: Subject to compliance with requirements, provide MAG-RITE II by Walltakers (800-820-9255); smooth, low gloss vinyl surface for projection and dry erase markers. ER50: 49/50 inch width, non-woven backing. White.

## 2.4 ACCESSORIES

- A. Adhesive: Mildew-resistant, nonstaining adhesive, for use with specific wall covering and substrate application indicated and as recommended in writing by wall-covering manufacturer.
1. Adhesive shall have a VOC content of 50 g/L or less.
  2. Adhesive shall comply with the testing and product requirements of the California Department of Public Health's (formerly, the California Department of Health Services') "Standard Method for the Testing and Evaluation of Volatile Organic Chemical Emissions from Indoor Sources Using Environmental Chambers."
    - a. Retain "Primer/Sealer" Paragraph below if required by substrate conditions, and insert primer requirements in the appropriate painting Section or revise and insert requirements here.
    - b. Primer/Sealer: Mildew resistant, complying with requirements in Section 099123 "Interior Painting" and recommended in writing by primer/sealer and wall-covering manufacturers for intended substrate.
- B. Seam Tape: As recommended in writing by wall-covering manufacturer.

## PART 3 – EXECUTION

### 3.1 EXAMINATION

- A. Examine substrates and conditions, with Installer present, for compliance with requirements for levelness, wall plumbness, maximum moisture content, and other conditions affecting performance of the Work.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

### 3.2 PREPARATION

- A. Comply with manufacturer's written instructions for surface preparation.
- B. Clean substrates of substances that could impair bond of wall covering, including dirt, oil, grease, mold, mildew, and incompatible primers.
- C. Prepare substrates to achieve a smooth, dry, clean, structurally sound surface free of flaking, unsound coatings, cracks, and defects.

1. Moisture Content: Maximum of 5 percent on new plaster, concrete, and concrete masonry units when tested with an electronic moisture meter.
2. Plaster: Allow new plaster to cure. Neutralize areas of high alkalinity. Prime with primer recommended in writing by primer/sealer manufacturer and wall-covering manufacturer.
3. Metals: If not factory primed, clean and apply primer recommended in writing by primer/sealer manufacturer and wall-covering manufacturer.
4. Retain "Gypsum Board" Subparagraph below if priming of gypsum-board surfaces is not performed as Work of another Section.
5. Gypsum Board: Prime with primer as recommended in writing by primer/sealer manufacturer and wall-covering manufacturer.
6. Painted Surfaces: Treat areas susceptible to pigment bleeding.
  - a. Check painted surfaces for pigment bleeding. Sand gloss, semigloss, and eggshell finish with fine sandpaper.
  - b. Remove hardware and hardware accessories, electrical plates and covers, light fixture trims, and similar items.
  - c. Acclimatize wall-covering materials by removing them from packaging in the installation areas not less than 24 hours before installation.

### 3.3 WALL-COVERING AND DRY ERASE BOARD INSTALLATION

- A. Comply with wall-covering manufacturers' written installation instructions applicable to products and applications indicated.
- B. Cut wall-covering strips in roll number sequence. Change the roll numbers at partition breaks and corners.
- C. Install strips in same order as cut from roll.
  1. For solid-color, even-texture, or random-match wall coverings, reverse every other strip.
- D. Install wall covering without lifted or curling edges and without visible shrinkage.
- E. Install seams vertical and plumb at least 6 inches (150 mm) from outside corners 6 inches (150 mm) from inside corners unless a change of pattern or color exists at corner. Horizontal seams are not permitted.
- F. Trim edges and seams for color uniformity, pattern match, and tight closure. Butt seams without overlaps or gaps between strips.
- G. Fully bond wall covering to substrate. Remove air bubbles, wrinkles, blisters, and other defects.

### 3.4 CLEANING

- A. Remove excess adhesive at seams, perimeter edges, and adjacent surfaces.
- B. Use cleaning methods recommended in writing by wall-covering manufacturer.
- C. Replace strips that cannot be cleaned.

- D. Reinstall hardware and hardware accessories, electrical plates and covers, light fixture trims, and similar items.

**END OF SECTION**